



Spark Plug Wire Set



Universal Wire Sets are 40" long with double 90° spark boots. Simply cut to the desired length and install coil terminal clips supplied. Available in copper or suppression core.

- | | | |
|---------------|--------------|----------------|
| VT No. | Color | Type |
| 32-0647 | Yellow | Suppression |
| 32-0648 | Yellow | Copper |
| 32-0650 | Orange | Copper |
| 32-0651 | Black | Suppression |
| 32-1123 | Red | Suppression |
| 32-7133 | Red | Copper, 5 pack |
| 32-0696 | Black | Copper |



Universal 8mm Pro Spark Plug Kits feature 24" wire leads with either 90° or 180° molded plug boots and straight coil boots with brass terminals. Wires feature the Spiro-Pro design which provides 10 times the firepower of carbon core wires and heat protection to 600°F. Works with electronic or points style ignition. All wires have a resistance factor of 350 ohms/ft. Great for magnetos, distributors or dual plug heads.

- | | |
|-----------------|------------------|
| 90° Kits | Color |
| 32-6081 | Black |
| 32-6281 | Red |
| 32-6481 | Yellow |
| 32-6681 | Blue |
| 32-6381 | Purple |
| 32-6085 | Black (180° Kit) |



Sifton 8mm Universal Wire Set features carbonite suppression core cut to 2 24" lengths.

- | | |
|---------------|--------------|
| VT No. | Color |
| 32-1041 | Red |
| 32-1042 | Black |



Sumax Colored 8mm Plug Wires by Taylor are pre-cut and have the plug/coil boots and terminals already installed. Designed for electronic ignition, but work great on point types.

Color	1984-99 FXST FXD	1982-94 FXR	1980-98 FLT	2000-up FXST- FLST- FXD	1999-06 FL with Carb Only	1999- 08 FLT with EFI	2009-16 FLT
Red	32-7231*		32-7233	32-2023	32-2024	32-2015	32-2017
Purple				32-2033			
Blue	32-7631*			32-2063	32-2064		
Black	32-7031*	32-7035	32-7033	32-2003	32-2004	32-2016	32-2018
Yellow	32-7431*			32-2043	32-2044		

*Note: with coil adjacent to oil tank Dynaglide.



Sumax Thunder Volt 50 Black Wire Sets feature a ferrite spiral wound coated core that is a blend of copper/nickel alloy bonded by a conductive acrylic latex cover. This process is designed to reinforce and assist in holding core resistance to 50 ohms. The fat 10.4 mm (.409") wires also feature three layers of pure zimplex silicone, 600 degrees of heat protection, 102,000 volts dielectric strength with a tightly woven heat treated fiberglass braid and black pro boots bonded to the black with gold lettering wires.

- | | | |
|--------------|---------------|-------------------------------------|
| 8.2mm | 10.4mm | Fits |
| 32-5202 | 32-0031 | 1984-99 FXST, 1991-98 Dynaglide |
| 32-5206 | 32-0033 | 1980-98 FLT |
| 32-5207 | 32-0035 | 1984-94 FXR |
| 32-5208 | 32-5608 | 24" Universal 2 Piece with 90° boot |
| 32-5204 | 32-2032 | 1999-08 FLT with carburetor |
| | 32-2031 | 2000-up FXST, 1999-up Dynaglide |
| 32-5209 | 32-5200 | 2009-16 FLT |
| 32-5205 | 32-5203 | 1999-08 FLT with Fuel Injection |
| 32-5210 | | 12" Universal |



Important Note: Some items on this page may be emission-related parts subject to California or other emission control laws. Please see note on page 71 for important information regarding emission control regulatory compliance and warranty information.

