



Primary Chain



Diamond Endless Primary Chains

VT No.	Size	Year	Model
19-0361	428x2-76	1979-06	FLT-FXR
19-0368	428x2-74	1994-06	FLT
19-0360	428x2-82	1986-06	Softail
		1991-05	FXD
19-0786	428x2-92	2007-up	Softail
19-0583	428x2-86	2007-up	FLT

Primary Chains for XL.

VT No.	Year	Brand	Length
19-0362	1957-03	Diamond	94
19-0932	1957-03	TYK	94
19-0369	2004-up	Diamond	96

Rear Chain



"530 QR" Solid Roller Chains is a solid roller chain recommended exclusively for motorcycles originally equipped with non-O-Ring chain. Heat treated and shot peened for greater durability, pre-stressed and pre-stretched to minimize initial stretch.

QR	Size
19-0512	108
19-0514	112
19-0559	130



Replacement Safe-T-Lock Spring Clip for use with any Tsubaki as an added safety precaution. Assures the master link does not come apart and adds extra strength to the master link. This clip should not be used more than once, 50 pack.
VT No. 19-0551



530 Sigma O-Ring Chain with **10,600 lbs.** tensile strength, features heavy-duty, wide-waist link plates for increased durability. Solid and projected shouldered bushings utilize Tsubaki's unique

Micron Control technology for concentricity and cylindrical accuracy. Micron Control production technology has decreased initial stretch to .01% and increased wear life up to 100% over conventional chain. Sigma is perfectly proportioned to provide extraordinary strength with minimum weight.

Standard		Standard	
S Series	Size	S Series	Size
19-0540	102	19-0554	130
19-0541	104	19-0555	150
19-0542	106	19-0547	Connecting Link
19-0543	108		
19-0545	112		



530 HSL Tsubaki is a virtually maintenance free chain that has heavy duty shot-peened side plates sintered metal bushings and quad-staked riveting.

Nickel-plated HSL/NP is available in a gleaming rustless finish. Average tensile strength: 7,040 lbs. HSL series is recommended exclusively for bikes originally equipped with non O-Ring chain.

HSL	Size
19-0528	110
19-0529	112
19-0530	120
19-0531	Connecting Link