



# 300 RSD Frame



**300 Right Side Drive Chopper Frame by Wyatt Gatling** features full rigid styling with single or double tube motor carriage. Frame will accept round oil tank and up to 4" extended gas tanks. Neck is drilled for internal stop kit. Motor and transmission are in the stock position and no offset is required when using the right side drive transmission. 1" axle included. Both styles include billet front motor mount. The **51-3502** 300 Series features 1 3/8" tubing with 1 1/2" backbone. **51-3502** features 4" stretch in backbone and 6" in downtubes.

**VT No. 51-3502**

#### Recommended Parts List.

VT No.	Type	
20-0586	Belt 1.125" 133T	17-0455 Transmission
44-0669	Adjuster, 2 piece	44-0688 330 Right Side Spacer
44-0676	Axle (300)	44-0689 330 Left Side Spacer
52-0682	Wheel (or 52-0684) (300)	27-1729 Kickstand Stop
46-0709	Tire, Avon (300)	27-1785 Weld On Kickstand



**Frames include a one piece billet front mount which bolts in.**



51-3501

**Single Tube Chopper Frame** features full rigid styling by Wyatt Gatling. Frame will accept round oil tank, and up to 4" stretch gas tanks. Neck is drilled for internal stop kit. Frame has built in 3/4" offset to accommodate the 200 tire. Order inner primary or motor spacer plate with 3/4" offset. Frame details include: 1 3/8" tubing, billet rear axle plates, billet front motor mount, accepts 200 series tires w/1.5" belt, 4" stretch in downtubes, 38° rake, 2" stretch (backbone). Axle included.

**VT No. 51-3501**

**Order related components separately.**

VT No.	Item
44-0393	Rear Axle
20-0478	133T Belt (1.5")
20-0586	133T Belt (1.125")
19-0564	Alternator Flange Offset Plate
44-0669	Wheel Adjuster Set
40-0476	Chrome Oil Tank
40-0477	Raw Oil Tank



**Transmission Mounting Plate for Paughco Frame 51-0113** which is not available.

**VT No. 17-9957**

# 200 Frame



51-2050

**200 Wide Drive Frame** available with Bob mounts. Features rake of 34 degrees. 4" stretch downtubes. Made of 1026 DOM (Drawn Over Mandrel) steel tubing. Legs are 1.25" outside diameter with .125" thick wall. Backbone is

1.500" outside with .187" thick wall. Seat post is 1.500" with .187" wall. Included additionally rear axle and front oil tank mounts. Special features include TIG welded at stress points. Accepts 9" fender and 1984-up flat side gas tanks. Accepts Softail style oil tank, Softail style rear brake 87-up and up to 200 series tire with belt. Accepts 200 series tire with use of 1/2" offset kit not included. **VT No. 51-2050**